


# TRX-Q-77

## Diesel Generator



# TEREX

## DIESEL



### Generator Features

- 4 stroke 1500 rpm water cooled heavy duty diesel engine
- Radiator capable of cooling up to 50 °C
- 4-pole synchronous type, single bearing, brushless alternator
- Flexible fuel hoses and oil drain valve
- Welded steel sheet, powder coated electrostatic powder coated chassis
- Dry type replaceable air filter
- MEngine jacket water heater
- Chassis integrated fuel tank
- Industrial type silencer
- Electronic battery charger
- Electric circuit diagram
- Operation and maintenance manual
- Manual start protection system
- Battery and cables

### Prime Power

Limited time operating power under variable load. It is used as backup power in case of mains power outages. Overloads are not allowed.

### Standby Power

Continuous operating power under variable load. According to ISO 3046 standard, 10% overload is allowed in 12 hours operation.

### Jeneratör Özellikleri

		Prime	Stand-by
Power	kVA	65	77
Power	kW	52	57
Generator Model	TEREX-Q / TRX-Q-77		
Engine Model	QZH4105ZD		
Fuel Type:	Diesel		
Frequency	50 Hz		
Power Factor	Cos $\Phi$ = 0.8		
Voltaj:	400/231 V		

Dimensions		With Cabin	Without cabin
Lenght	mm	2350	1850
Heigh	mm	1730	1350
Width	mm	1100	950
Weight	kg	1275	1095
Fuel Tank Capacity	lt	140	150

H: External

K: Container

TBA: to be added



# TEREX

## DIESEL

0850 532 63 20  
Dudullu OSB Mah. İmes B Blok, 205.sk. No:31 Ümraniye/İstanbul

| [www.terexgen.com.tr](http://www.terexgen.com.tr)

# TRX-Q-77

## Diesel Generator



# TEREX

## DIESEL

### Engine

Engine Brand		QUARTZ
Engine Model:		QZH4105ZD
Engine Type:		4 Stroke Diesel Engine
Engine Stan-by Power:	kWm	60,5
Engine Prime Prime:	kWm	55
Cylinder Arrangement:		4L
Total Cylinder Arrangement:	lt	4,1
Cooling System:		Water
Broke-Stroke:	mm	105 x 118
Compression Ratio:		18:1
Aspiration:		Turboşarj, Intercooler
Governör Type:		Electronic
Elektrical System:	VDC	12
Lubricant Oil Capacity:	lt	12,5
Coolant Capacity:	lt	17
Frequency Lt:	Hz - d/dk	50 - 1500
Jacket Water Heater:	quantityx W	1 x 1000
Battery:	quantity x AH	1 x 72
Charge Alternator Current:	A	TBA
Injection System:		Direct
Cooling Air Flow:	m <sup>3</sup> /dk	115
Combustion Air Flow:	m <sup>3</sup> /dk	4,1
Exhaust Gas Flow:	m <sup>3</sup> /dk	12,1
Exhaust Gas Temperature:	°C	600
Fuel Consumption Under 100% Load:	lt/s	14,4
Fuel Consumption Under 75% Load:	lt/s	10,8
Fuel Consumption Under 50% Load:	lt/s	7,4

### Alternetör

Phase / Pole Number:		3/4+
Excitation System:		Self Excited, Brushless
Voltage Regulator:		A. V. R. (Automatic)
Voltage Regulation:		±%1
Insulation Class:		H
Protection Class:		IP23
Connection Type:		Star
Frequency:	Hz	50
Power Factor:		Cos $\Phi$ = 0,8
Total Harmonic Distortion (No Load):		< % 3.5
Output Voltage:	VAC	231/400

TBA: to be added



# TEREX

## DIESEL



0850 532 63 20

Dudullu OSB Mah. İmes B Blok, 205.sk. No:31 Ümraniye/İstanbul

| [www.terexgen.com.tr](http://www.terexgen.com.tr)

# TRX-Q-77


## Diesel Generator



# TEREX

## DIESEL

### Control Panel



**Datakom D300**

#### Datakom D300 Automatic Control Module

AMF function ATS function

Remote start function Manual start function Engine control function

Suitable for remote monitoring

#### Mains and Genset LL- LN Voltages

Mains and generator frequency Mains and genset phase currents Mains and generator neutral currents

Grid and generator phase and total, kW, kVA, kVAR  
Power factor, engine speed, battery voltage and more

#### Connections

3 phase 4 wire, stars & delta

3 phase 3 wire, 2 current transformer

2 phase 3 wire

1 phase 2 wire

#### Communication

RS232 – 485 connection with cable J1939-CANBUS

GSM / GPRS connection Ethernet connection

Modbus RTU

#### Protection Functions

- Overvoltage
- Low voltage
- Voltage asymmetry and phase sequence High frequency
- Low frequency Short-circuit current Overcurrent
- Power factor
- Coolant temperature Low oil pressure

#### Auto Panel Features

- Automatic generator, grid control and fault monitoring Easy control with a user-friendly interface from the panel screen
- Remote operation with optional communication cards Manual programming with password-protected service interface
- Manual control of generator and transfer panel with buttons on the front panel
- Front panel protection class IP65
- **With an operating temperature of -20 C to +70 C and a storage temperature of -40 C to +80 C**



# TEREX

## DIESEL

0850 532 63 20

Dudullu OSB Mah. İmes B Blok, 205.sk. No:31 Ümraniye/İstanbul

| [www.terexgen.com.tr](http://www.terexgen.com.tr)